



- Capacity from 4 to 50 Tn, stroke up to 53 mm.
- Models with two, three and four stages.
- Load return.
- For use in confined spaces: machinery positioning, tool fastening.
- Mounting bolt holes for easy fixing.
- All models are black nitrated.

Capacity		Stages	Stroke	Model	Oil Cap.	Closed Height	Extended Height	Weight
Tn	kN	No.	mm	LARZEP	cm ³	mm	mm	kg
4	42	2	21,5	SLX00422	22,4	43,5	65,0	1,5
		3	32,0	SLX00432	58,1	53,5	85,5	2,9
		4	53,5	SLX00454	199,9	71,0	124,5	6,9
10	100	2	21,5	SLX01022	51,7	53,5	75,0	2,9
		3	43,0	SLX01043	193,5	71,0	114,0	6,9
30	287	2	31,0	SLX03031	176,1	71,0	102,0	6,9
50	487	2	33,0	SLX05033	342,5	87,0	120,0	14,6

Capacity	Model	1st Stage			2nd Stage			3rd Stage			4tg Stage		
		Cap.	Stroke	Area	Cap.	Stroke	Area	Cap.	Stroke	Area	Cap.	Stroke	Area
Tn	LARZEP	kN	mm	cm ²	kN	mm	cm ²	kN	mm	cm ²	kN	mm	cm ²
4	SLX00422	100	11	14,5	42	10,5	6,15	-	-	-	-	-	-
	SLX00432	228	11	33,1	100	10,5	14,5	43	10,5	6,15	-	-	-
	SLX00454	488	16	70,8	287	15,0	41,8	100	12,0	14,5	42	10,5	6,15
10	SLX01022	228	11	33,1	100	10,5	14,5	-	-	-	-	-	-
	SLX01043	488	16	70,8	287	15	41,8	100	12	14,5	-	-	-
30	SLX03031	488	16	70,8	287	15	41,8	-	-	-	-	-	-
50	SLX05033	954	16	138,9	487	17	70,8	-	-	-	-	-	-